

## CUBE Next light tower

The CUBE Next light tower is a new battery-powered model that has been designed to attain the highest levels of performance and safety with total respect for the environment. Providing the longest range in battery-powered lighting towers, we have set the standard.

## Generac LED floodlights with adjustable light power

4x240 W high-efficiency **New G4 LED floodlights** designed by Generac Mobile®. Special version with adjustable light power output.

## Automatic Mode fitted as standard

The digital timer and the darkness sensor are installed as standard so that the CUBE Next can automatically start and stop.

## Zero noise and carbon dioxide emission

When the CUBE Next light tower is powered through the battery pack, it is **completely silent and doesn't emit carbon dioxide** (CO<sub>2</sub>). An ideal solution for events and working areas with low noise or CO<sub>2</sub> emission requirements.

## Running time & Illumination!

Thanks to the dimmable LED lamps set to the minimum value, this model can run **from 17 to 95 hours** before recharging the battery pack. Instead if the requirement is to obtain the widest illuminated area, by setting the dimmer knob at 100% the CUBE Next can illuminate 3100 m<sup>2</sup>.

## Bolted Frame with top accessibility

The CUBE Next light tower has a new **bolted frame** for much better resistance to vibrations, wear, and rust. It offers the best reliability and durability in the industry. The new adjustable locking system embedded in the machine frame. A step forward from the competition standard locking system. No more removable external lockers, when CUBE Next doors are locked, it's impossible to change position or even remove stabilizers.

4 wide doors provide complete access to the technical area.



*Picture shown may not reflect actual configuration.*

# CUBE NEXT 4X240W

4x240W LED

LIGHT TOWERS  
ELECTRIC LINE

GENERAC® MOBILE

## SPECIFICATIONS

CUBE Next 4x240W	Technical Data				
Minimum dimensions (L x W x H)	1230 x 1160 x 2405 mm				
Maximum dimensions (L x W x H)	1790 x 1735 x 8400 mm				
Weight	1285 kg				
Mast lifting system	Hydraulic				
Mast rotation	340°				
Dimmer switch	OFF	25%	50%	75%	100%
Lamps power	0	4 x 60 W	4 x 120W	4 x 180W	4 x 240 W
Lamps type	G4 LED				
Luminous flux	–	41040 Lm	76184 Lm	107668 Lm	139200 Lm
Illuminated area	–	1500 m <sup>2</sup>	2200 m <sup>2</sup>	2700 m <sup>2</sup>	3100 m <sup>2</sup>
Battery running time	–	94 h	47 h	24 h	17 h
Battery charging time	9 h	14 h	12 h	11 h	11 h
CEE inlet plug (A/V/Hz)	32/230/50 – 32/240/60				
Avg. sound pressure	0				
Wind speed resistance	110 km/h				



Picture shown may not reflect actual configuration.