

# SPECIFICATIONS

#### **CUBE PRO Lithium lighting tower**

CUBE PRO is not just a new lighting tower, but the authentic and unique "ALL IN ONE" product. It embodies all the innovations and new technologies that Generac Mobile® has developed in 25 years at the top of the industry as a manufacturer. Generac Mobile® has brought together all the Rental needs, in one single product.

CUBE PRO has been designed following the most actual sustainability path and offers global connectivity for remote control.

## Li-ion Battery

CUBE PRO Lithium is equipped with an **Li-ion battery pack**, an innovative battery technology with a high rate of charge and excellent performance at higher temperatures.

### **ALL IN ONE**

CUBE PRO is truly the Complete Solution, the only one to offer altogether: **the future**, with 100% battery-powered supply; **the present**, with the latest generation Generac Mobile<sup>®</sup> hybrid power supply; **the tradition**, with low consumption diesel engines. All in one model.



4×240 W high-efficiency **New G4 LED floodlights** designed by Generac Mobile<sup>®</sup>. Special version with adjustable light power output from 25% to 100%.

### Anti-glare floodlights

The floodlights can be equipped with optional antiglare shells to create a soft, ambient light for use on special applications like roadworks, airports and where light pollution must be kept to a minimum.

#### Control panel

Control panel with digital controller and easy Function Selector:

- Off
- Manual mode
- · Darkness sensor mode
- · Timer mode

#### Plug-in system

Generac Mobile® can provide customers with two external accessories:

- I-Extender PRO A stand-alone, stackable, battery pack with 25 kWh capacity that will make CUBE PRO runs up to 40 hours in Battery mode. Standard: CEE 16A outlet socket.
- Solar kit PRO A stackable solar panel kit with 3×300 Wp sliding solar panels able
  to recharge the CUBE PRO battery, reducing the use of the generator or other power
  sources. Multipin outlet socket

The operator can easily connect these devices to the CUBE PRO to the inlet sockets installed as default on the machine.

It's also possible to connect the unit to the Mains through the inlet socket (standard CEE 16A).

#### **Transportability**

The squared shape allows to load up to 22 units on a 13 meters truck, and up to 18 units on a 40' container.



Picture shown may not reflect actual configuration.



**SPECIFICATIONS** 

	Technical				
CUBE PRO Y2 Lithium	Data				
Min. dimensions	1230 x 115	1230 x 1150 x 2383 mm			
Max. dimensions	1793 x 173	1793 x 1737 x 8100 mm			
Dry weight	1175 kg	1175 kg			
Engine model	Yanmar 2T	Yanmar 2TNV			
Cylinders (q.ty)	2	2			
Engine cooling	Liquid	Liquid			
Engine speed (50/60hz)	1500 / 180	1500 / 1800 RPM			
Sound pressure	0 – 58	0 – 58			
Dimmer switch	25%	50%	75%	100%	
Max. lamps power	4x60W	4x120W	4x180W	4x240W	
Lamps type	G4 LED	G4 LED	G4 LED	G4 LED	
Max. total lumen	41040 Lm	76184 Lm	107668 Lm	139200 Lm	
Max. illuminated area	1500 m <sup>2</sup>	2200 m <sup>2</sup>	2700 m <sup>2</sup>	3100 m <sup>2</sup>	
Battery recharging time	4h 29'	4h 41'	5h 09'	5h 48'	
Running time – Battery	19h 31'	11h 07'	6h 15'	4h 44'	
Running time – Generator	275 h	252 h	224 h	208 h	
Running time – Hybrid	840 h	521 h	330 h	263 h	
Lifting system	Hydraulic	Hydraulic			
Mast rotation	340°	340°			
Wind resistance	110 km/h	110 km/h			
Alternator (kVA/V/Hz)	5/220/50 -	5/220/50 - 5/240/60			
CEE inlet plug	<b>V</b>	√			
Multipin inlet plug	<b>V</b>	√			
Tank capacity (gross)	160 litres (	160 litres (150 net)			
Liquid containment (110%)	√	1			



Picture shown may not reflect actual configuration.